

Wagon type: Rens with hinged sides

	type: 70mm WOODEN FLOOR	type: 8mm STEEL FLOOR																																																
PAYLOAD	type: 70mm WOODEN FLOOR	type: 8mm STEEL FLOOR																																																
Load limits	<table border="1"> <thead> <tr> <th></th> <th>A</th> <th>B</th> <th>C</th> <th>D</th> </tr> </thead> <tbody> <tr> <td>S</td> <td>39,4</td> <td>47,4</td> <td>55,4</td> <td>65,4</td> </tr> <tr> <td>120</td> <td colspan="4">00,0</td> </tr> </tbody> </table>		A	B	C	D	S	39,4	47,4	55,4	65,4	120	00,0				<table border="1"> <thead> <tr> <th></th> <th>A</th> <th>B</th> <th>C</th> <th>D</th> </tr> </thead> <tbody> <tr> <td>S</td> <td>39,4</td> <td>47,4</td> <td>55,4</td> <td>65,4</td> </tr> <tr> <td>120</td> <td colspan="4">00,0</td> </tr> </tbody> </table>		A	B	C	D	S	39,4	47,4	55,4	65,4	120	00,0																					
	A	B	C	D																																														
S	39,4	47,4	55,4	65,4																																														
120	00,0																																																	
	A	B	C	D																																														
S	39,4	47,4	55,4	65,4																																														
120	00,0																																																	
Tare weight	24,6t	24,6t																																																
DIMENSIONS																																																		
Length over buffers	19.900mm	19.900mm																																																
Distance between bogie centres	1.800mm	1.800mm																																																
Load Area	49,0m ²	49,0m ²																																																
Loading length	18.500mm	18.500mm																																																
Loading width	2.650mm	2.650mm																																																
Height of floor	1.260mm	1.198mm																																																
TECHNICAL DATA																																																		
Bogie	Y25Ls1 (K)	Y25Ls1 (K)																																																
Handbrake	if present, from ground	operated from the ground																																																
Wheelsets	BA 004	BA ULT 25																																																
Axle load	22,5t	22,5t																																																
Brake	KE-GP-A 12"	KE-GP-A 12"																																																
Max Brake Load	58t (contin. Autom.)	58t (contin. Autom.)																																																
OPERATION																																																		
Gauge	TEN/G1	TEN GE/G1																																																
Smallest navigable track curve (single car)	35m	35m																																																
Ramp angle	2,5°	2,5°																																																
EQUIPMENT	16 UIC swivel stanchions	16 short UIC swivel stanchions																																																
	18 folding flaps, 2 front flaps (520mm height)	18 folding flaps, 2 folding front flaps																																																
	20 Rings at the floor	36 rings outside at the framework																																																
		4 rings outside at each front flap																																																
		1 ring inside at each side flap																																																
LOAD	Wood and Steel Products	Sand, Gravel																																																
HEAVY SINGLE LOADS	<table border="1"> <thead> <tr> <th></th> <th>m</th> <th>t</th> <th>xx</th> </tr> </thead> <tbody> <tr> <td>a-a</td> <td>2,0</td> <td>32</td> <td>33</td> </tr> <tr> <td>b-b</td> <td>5,0</td> <td>39</td> <td>44</td> </tr> <tr> <td>c-c</td> <td>9,0</td> <td>42</td> <td>52</td> </tr> <tr> <td>d-d</td> <td>15,0</td> <td>62</td> <td>65</td> </tr> <tr> <td>e-e</td> <td>18,0</td> <td>65</td> <td>28</td> </tr> </tbody> </table>		m	t	xx	a-a	2,0	32	33	b-b	5,0	39	44	c-c	9,0	42	52	d-d	15,0	62	65	e-e	18,0	65	28	<table border="1"> <thead> <tr> <th></th> <th>m</th> <th>t</th> <th>xx</th> </tr> </thead> <tbody> <tr> <td>a-a</td> <td>2,0</td> <td>32</td> <td>33</td> </tr> <tr> <td>b-b</td> <td>5,0</td> <td>39</td> <td>44</td> </tr> <tr> <td>c-c</td> <td>9,0</td> <td>42</td> <td>52</td> </tr> <tr> <td>d-d</td> <td>15,0</td> <td>62</td> <td>65</td> </tr> <tr> <td>e-e</td> <td>18,0</td> <td>65</td> <td>28</td> </tr> </tbody> </table>		m	t	xx	a-a	2,0	32	33	b-b	5,0	39	44	c-c	9,0	42	52	d-d	15,0	62	65	e-e	18,0	65	28
	m	t	xx																																															
a-a	2,0	32	33																																															
b-b	5,0	39	44																																															
c-c	9,0	42	52																																															
d-d	15,0	62	65																																															
e-e	18,0	65	28																																															
	m	t	xx																																															
a-a	2,0	32	33																																															
b-b	5,0	39	44																																															
c-c	9,0	42	52																																															
d-d	15,0	62	65																																															
e-e	18,0	65	28																																															



ZUG RENTALS

