

Wagon type: Shimms																												
<b>PAYLOAD</b>																												
Load limits	<table border="1"> <thead> <tr> <th></th> <th>A</th> <th>B1</th> <th>B2</th> <th>C2</th> <th>C3 C4</th> <th>D2</th> <th>D3</th> <th>D4</th> </tr> </thead> <tbody> <tr> <td>S</td> <td>38,7</td> <td>38,7</td> <td>50,5</td> <td>55,6</td> <td>58,5</td> <td>55,6</td> <td>65,2</td> <td>68,5</td> </tr> <tr> <td>120</td> <td colspan="8">00,0 t</td> </tr> </tbody> </table>		A	B1	B2	C2	C3 C4	D2	D3	D4	S	38,7	38,7	50,5	55,6	58,5	55,6	65,2	68,5	120	00,0 t							
	A	B1	B2	C2	C3 C4	D2	D3	D4																				
S	38,7	38,7	50,5	55,6	58,5	55,6	65,2	68,5																				
120	00,0 t																											
Tare weight	21,5t (with handbrake 21,6t)																											
<b>DIMENSIONS</b>																												
Length over buffers	12.040mm																											
Loading width	max. 2.400mm between the securing arms: 352 - 2.052mm																											
Distance between bogie centres	1.800mm																											
Loading diagram	<table border="1"> <thead> <tr> <th>cradle</th> <th>1</th> <th>2</th> <th>3</th> <th>4</th> <th>5</th> </tr> </thead> <tbody> <tr> <td>Ø min mm</td> <td>1000</td> <td>800</td> <td>1000</td> <td>800</td> <td>1000</td> </tr> <tr> <td>Ø max mm</td> <td>2200</td> <td>1650</td> <td>2650</td> <td>1650</td> <td>2200</td> </tr> <tr> <td>t max</td> <td>34 t</td> <td>17 t</td> <td>45 t</td> <td>17 t</td> <td>34 t</td> </tr> </tbody> </table>	cradle	1	2	3	4	5	Ø min mm	1000	800	1000	800	1000	Ø max mm	2200	1650	2650	1650	2200	t max	34 t	17 t	45 t	17 t	34 t			
cradle	1	2	3	4	5																							
Ø min mm	1000	800	1000	800	1000																							
Ø max mm	2200	1650	2650	1650	2200																							
t max	34 t	17 t	45 t	17 t	34 t																							
<b>TECHNICAL DATA</b>																												
Bogie	Y25Lsd1 (K)																											
Handbrake	if present, operated from ground																											
Wheelsets	BA 004																											
Axle load	22,5t																											
Brake	KE-GP-A 12"																											
Max Brake Load	58t																											
<b>OPERATION</b>																												
Gauge	TEN-RIV G1																											
Ramp angle	2,5°																											
Smallest navigable track curve (single car)	35m																											



**ZUG RENTALS**

